



150MB

Wheeled Dry Chemical Stored Pressure Extinguishers

- Welded heavy tubular steel frame protects cylinder and valve.
- Tow ring permits vehicle towing.
- 16" semi-pneumatic tires. 4" width.
- DOT 4BW-240 Cylinder. 480 PSI test pressure.
- Chrome plated brass valve. Cam actuated.
- 50' hose. Ball bearing swivel joint.
- Corrosion resistant red enamel finish.
- Cylinder easily removed from frame. All stainless steel mounting hardware.

These extinguishers are designed for front line fire protection where high fire hazard and the potential for loss makes quick, effective, on-site response essential. When dry chemical is the preferred agent, these units provide dependable, affordable protection. Well balanced for easy maneuverability, they are highly mobile and may be operated by a single individual. Long range discharge and high fire fighting ratings gives protection to the operator and access to ordinarily out-of-reach fires. High hazard locations such as chemical and petroleum processing plants and storage facilities, construction sites, and warehouses are but a few of the areas where these large wheeled stored pressure dry chemical extinguishers are recommended. Available in all three of the principal dry chemicals — ABC (ammonium phosphate base), Regular (sodium bicarbonate base), and Purple-K (potassium bicarbonate base).



MODEL 150MB



MODEL 150RB MODEL 150PB

SPECIFICATIONS

Model No.	Nominal Capacity Lbs. (kg)	AGENT	Discharge Time	Discharge Range Feet (meters)	Overall Height Inches (cm)	Overall Width Inches (cm)	Overall Length Inches (cm)	Wheel Diameter Inches (cm)	U/L Rating
150 MB	125 (56.7)	ABC	45 Sec.	30-40 (9.1-12.2)	58 (147.3)	28 (71.1)	40 (101.6)	16 (40.6)	40A-240B:C
150 RB	150 (68)	REGULAR	55 Sec.	30-40 (9.1-12.2)	58 (147.3)	28 (71.1)	40 (101.6)	16 (40.6)	240B:C
150 PB	125 (56.7)	PURPLE-K	48 Sec.	30-40 (9.1-12.2)	58 (147.3)	28 (71.1)	40 (101.6)	16 (40.6)	240B:C

TECHNICAL DATA

125 & 150 Pound Stored Pressure Dry Chemical Extinguisher

MODEL NUMBER	150-MB	150-RB	150-PB
NOMINAL (LBS) CAPACITY (KILOGRAMS)	125 56.7	150 68	125 56.7
U/L FIRE RATING	40A-240B:C	240B:C	240B:C
AGENT TYPE	ABC	REGULAR	PURPLE K
ITEM PART NUMBER	20653	20677	20684
VALVE MATERIAL	BRASS	BRASS	BRASS
SHELL MATERIAL	STEEL	STEEL	STEEL
SHIPPING (LBS) WEIGHT (KILOGRAMS)	300 136	375 170	300 136
OPERATING PRESSURE	240 PSI	240 PSI	240 PSI
TEMPERATURE RANGE (F)	-40° to 120°	-40° to 120°	-40° to 120°
DISCHARGE TIME (SECONDS)	45	55	48
DISCHARGE (FEET) RANGE (METERS)	30 - 40 9.1 - 12.2	30 - 40 9.1 - 12.2	30 - 40 9.1 - 12.2
UNIT (INCHES) HEIGHT (CENTIMETERS)	58 147.3	58 147.3	58 147.3
UNIT WIDTH (INCHES) (CENTIMETERS)	28 71.1	28 71.1	28 71.1

This information is subject to change without notice. While every effort has been made to eliminate errors, Badger Fire Protection disclaims any liability for any errors or misinterpretation of the information contained herein. Contact Badger Fire Protection or your local distributor for assistance.

Distributed by: