



CXL

UNIVERSAL CALLPOINT

The CXL Universal Call Point combines a number of features into one package, simplifying selection and reducing stock variants. Designed to provide the facilities most frequently used, the Universal is the easy answer for the majority of conventional installations.

- PROVEN DESIGN APPROVED AND CERTIFIED TO EN54-11
- SECURE & CONVENIENT CLIP FIT COVER
- USE OF GLASS OR PLASTIC RESETTABLE ELEMENT WITHOUT MODIFICATION
- SUPERIOR LED ALARM INDICATION
- BACK BOX
- WEATHERPROOF VERSION AVAILABLE
- KIT COMPRISES
 - A CXL call point with high visibility LED alarm indicator
 - Choice of connection for 470R or 680R resistors
 - Fitted glass element
 - Supplied resettable element with alarm flag
 - Unique Test / reset / cover removal key
 - Back box with fixing screws
 - Installation leaflet with drilling template for back box

Specification

Configuration	Series 470R or 680R resistor with LED alarm indicator. Resistor value selected by connection.
Rating	24Vdc systems
Connections	6-way terminal block (In & Out for each connection)
Operating Method	Glass element with printed plastic safety film or resettable plastic element with integral alarm indicator (Both elements are supplied and each can be fitted during installation)
Test/Reset Facility	Unique multi-function key
Construction	ABS FR
IP Rating	Indoor: IP42 Outdoor: IP66
Temperature	Indoor: -10°C to +55°C Outdoor: -25°C to +70°C
Weight	Indoor: 0.2Kg Outdoor: 0.3kg