

# BS EN3 CO2 Type Fire Extinguisher



PRESSURE EQUIPMENT DIRECTIVE  
APPROVED FIRE EXTINGUISHERS



0038/03

MARINE EQUIPMENT DIRECTIVE  
APPROVED FIRE EXTINGUISHERS



0038/03



CERTIFIED TO BS EN3  
LICENCE NO. KM 57533



Quality  
Endorsed  
Company

ISO 9001  
Certified



FEX182

FEX180


FEX183

FEX179

FEX178

FEX181

- British Standards Institution – BSI approval.
- Suitable for Class B & Electrical Hazards.
- High quality and good value.
- All handles colour coded for instant recognition.
- Available in aluminium and light weight steel.
- Easy to use and leave no messy residue.
- ISO 9002 Certified Quality System by QAS Australia.



## TECHNICAL SPECIFICATION

	2kg	5kg	2kg	5kg	2kg*	5kg*
EXTINGUISHER TYPE	2kg	5kg	2kg	5kg	2kg*	5kg*
MATERIAL	Steel	Steel	Aluminium	Aluminium	Steel	Steel
MODEL NO.	FEX182	FEX183	FEX180	FEX181	FEX178	FEX179
FIRE RATING	34B	55B	34B	55B	34B*	89B*
OPERATING TEMPERATURE	-20°C to 60°C				-30°C to 60°C	
OPERATING PRESSURE	50 Bar at 20°C					
CYLINDER SPECIFICATION	1997/23/EC					
HEIGHT	625mm	770mm	575mm	695mm	625mm	770mm
FULL WEIGHT	8.4kg	15.8kg	6.1kg	15.2kg	8.4kg	15.8kg
EMPTY WEIGHT	6.4kg	10.8kg	4.1kg	10.2kg	6.4kg	10.8kg
DISCHARGE TIME	14 secs	15 secs	14 secs	15 secs	14 secs	15 secs
RANGE OF THROW (approx)	4 - 5 M	4 - 5 M	4 - 5 M	4 - 5 M	4 - 5 M	4 - 5 M
CARTON SIZE mm	220 x 180 x 650	230 x 245 x 780	180 x 200 x 530	230x 240 x 720	220 x 180 x 650	230 x 245 x 780

\* Pending approval.

The products specified in this brochure are subject to continual development and improvement. Information in this brochure is subject to alteration without notice. All dimensions in mm unless otherwise specified.