

BS EN3 Powder Type Fire Extinguisher



PRESSURE EQUIPMENT DIRECTIVE
APPROVED FIRE EXTINGUISHERS



0038/03

MARINE EQUIPMENT DIRECTIVE
APPROVED FIRE EXTINGUISHERS



0038/03



CERTIFIED TO BS EN3
LICENCE NO. KM 57533



Quality
Endorsed
Company

ISO 9001
Certified



- British Standards Institution – BSI approval store powder and cartridge type.
- Suitable for Class A, B, C & electrical hazards.
- Ideal for industrial, commercial and domestic environment.
- High quality and good value.
- All handles stainless steel and colour coded for instant recognition.
- All units tested by electronic leak detection.
- Operated effectively at both high and low temperature.
- ISO 9001 Certified Quality System by QAS Australia.



TECHNICAL SPECIFICATION

EXTINGUISHER TYPE	1kg	2kg	4kg	6kg	9kg	6kg	9kg
	STORE PRESSURE TYPE (NITROGEN PROPELLANT)					CO2 CARTRIDGE	
MODEL NO.	FEX108	FEX104	FEX105	FEX106	FEX107	FEX109	FEX110
FIRE RATING	5A, 21B	13A, 55B	21A, 113B	27A, 144B	34A, 233B	34A, 233B	43A, 233B
OPERATING TEMPERATURE	-20°C to 60°C						
OPERATING PRESSURE	12 Bar		14 Bar				
HEIGHT	335mm	400mm	480mm	480mm	555mm	485mm	565mm
FULL WEIGHT	2.0kg	3.3kg	7.1kg	9.1kg	12.8kg	10.5kg	14.2kg
TEST PRESSURE	25 Bar						
DISCHARGE TIME	7 secs	10 secs	13 secs	19 secs	22 secs	20 secs	24 secs
RANGE OF THROW (approx)	4 - 5 M	4 - 5 M	5 - 6 M	5 - 6 M	5 - 6 M	5 - 6 M	5 - 6 M
CARTON SIZE mm	105 x 120 x 345	125 x 160 x 430	180 x 210 x 495	180 x 210 x 495	205 x 205 x 590	180 x 210 x 495	205 x 205 x 590