

BS EN3 Water & Foam Type Fire Extinguisher



PRESSURE EQUIPMENT DIRECTIVE
APPROVED FIRE EXTINGUISHERS



0038/03

MARINE EQUIPMENT DIRECTIVE
APPROVED FIRE EXTINGUISHERS



0038/03



CERTIFIED TO BS EN3
LICENCE NO. KM 57533



Quality
Endorsed
Company

ISO 9001
Certified



- British Standards Institution – BSI approval.
- Foam type is suitable for Class A & B.
- Water type is suitable for Class A.
- Protective plastic lining.
- All handles stainless steel and colour coded for instant recognition.
- High quality and good value.
- ISO 9001 Certified System by QAS Australia.



TECHNICAL SPECIFICATION

EXTINGUISHER TYPE	6L	9L	9L	9L	9L
	FOAM	FOAM	WATER	FOAM	WATER
	STORE PRESSURE TYPE (NITROGEN PROPELLENT)			CO2 CARTRIDGE	
MODEL NO.	FEX102	FEX103	FEX101	FEX112	FEX111
FIRE RATING	8A, 113B	13A, 183B	13A	13A, 183B	13A
OPERATING TEMPERATURE	5°C to 60°C				
OPERATING PRESSURE	12 Bar				
TEST PRESSURE	25 Bar				
HEIGHT	555mm	625mm	625mm	630mm	630mm
FULL WEIGHT	9.2kg	13.5kg	13.5kg	14.2kg	14.2kg
DISCHARGE TIME	50 secs	65 secs	61 secs	94 secs	89 secs
RANGE OF THROW (approx)	4 - 5 M	4 - 5 M	6 M	4 - 5 M	6 M
CARTON SIZE mm	190 x 210 x 565	200 x 200 x 646	200 x 200 x 645	200 x 200 x 645	200 x 200 x 645